צמוד קיר לבן UP&DOWN LEDVANCE
12W IP54 אור חם




סדרת גופי תאורה קיריים מבית LEDVANCE OSRAM העולמית.
הגופים מיוצרים מחומרים איכותיים בדרגת אטימות גבוהה IP54. מהווים תחליף חסכוני במיוחד בהוצאות חשמל ותחזוקה בהשוואה לגופי תאורה מסורתיים. התקנה בקלות ובנוחות. להארת היקפי מבנה, משטחים אנכיים, חזיתות מבנים, עמודים, חומות, מרפסות ועוד.

מק"ט - 10589403


דגם - 4058075214071

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IK06
- IP54
- CLASS1
- אייקון של 220-240 וולט 50-60 הרץ
- מוצר בדרגת PRO
- 5 שנות אחריות







DIMENSIONS & WEIGHT

Width	55mm
Length	90mm
Height	160mm
Product weight	480g

MATERIALS & COLORS

Cable surface [mm2]	white
Protection class IEC 62262	aluminum
Cover finishing	IK06
Cover material	Clear
Lens material	glass

ELECTRICAL DATA

Nominal wattage	12W
Nominal current	0.1A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver output current	260mA
Power factor	>0.50
Max. no. of lum. On circuit break. B16 A	75
Max. no. of lum. On circuit break. C10 A	96
Max. no. of lum. On circuit break. C16 A	60
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP54
Protection class IK 62262 (shock resistance)	IK06
Green Building	ISO 14001
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	-20...+40°C

PERFORMANCE

Lifespan (Hr)	30000Hrs

PHOTOMETRIC DATA

Luminous efficacy	58Lm/W
Luminous flux	700Lm
CCT	3000K
CRI	>80
LED manufacturer	CREE
Chip type	COB
Beam angle	280°
CIE class	General-Diffuse
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >