פאנל על הטיח לבן CLOCK 32W 40CM 3CCT



סדרת צמודי תקרה בעיצוב דק וביעילות אורית גבוהה 100Lm/W. אפשרות לשינוי גוון האור - חם, קר או ניטרלי. דרייבר איכותי ללא ריצוד, בסיס PC וכיסוי פרוסט מונע סנוור. התקנה קלה ונוחה בקליק על ידי סיבוב, וללא צורך בפתיחת הגוף.
להארה בחדרי מגורים, משרדים, שטחים מסחריים, מבואות, תאורה כללית ועוד.

מק"ט - 17700052
דגם - EW-X12-32W-WHITE-CCT3
קישור לדף מוצר ואביזרים נלווים באתר

2 YEAR GUARANTEE | 220-240V 50-60Hz | IP40 | IK07 | מתאים לדרישות התקן הישראלי



DIMENSIONS & WEIGHT מידות ומשקל

Height	25mm
Diameter	400mm
Product weight	1100g

MATERIALS & COLORS מבנה וגימור

Product color	White matte
Body material	ABS
Protection class IEC 62262	IK07
Cover finishing	milky
Cover material	PS

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	32W
Nominal current	0.14A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	ECO 2 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP40
Protection class IK 62262 (shock resistance)	IK07
Green Building	RoHS
ISO 9001	√

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Surface
Mounting location	Ceiling
Type of protection	IP40
Ambient temperature range	-10...+45°C

PERFORMANCE ביצועים

Lifespan (Hr)	25000Hrs

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	100Lm/W
Luminous flux	3200Lm
CCT	300/4000/6500K
CRI	>82
LED manufacturer	MLS
Chip type	SMD 2835
SDCM	≤6
Beam angle	120°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >