פאנל על הטיח לבן CLOCK 70W 70CM 3CCT



סדרת צמודי תקרה בעיצוב דק וביעילות אורית גבוהה 100Lm/W.
אפשרות לשינוי גוון האור - חם, קר או ניטרלי. דרייבר איכותי ללא ריצוד, בסיס PC וכיסוי פרוסט מונע סנוור. התקנה קלה ונוחה בקליק על ידי סיבוב, וללא צורך בפתיחת הגוף. להארה בחדרי מגורים, משרדים, שטחים מסחריים, מבואות, תאורה כללית ועוד.

מק"ט - 17700055

דגם - EW-X12-70W-WHITE-CCT3

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IK07
- IP40
- CLASS2
- אייקון של 220-240 וולט 50-60 הרץ
- שנתיים אחריות



DIMENSIONS & WEIGHT

Width	700mm
Height	27mm
Diameter	750mm
Product weight	4000g

MATERIALS & COLORS

Cable surface [mm2]	White matte
Protection class IEC 62262	ABS
Cover finishing	IK07
Cover material	milky
Lens material	PS

ELECTRICAL DATA

Nominal wattage	70W
Nominal current	0.3A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	ECO 2 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP40
Protection class IK 62262 (shock resistance)	IK07
Green Building	RoHS
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	-10...+45°C

PERFORMANCE

Lifespan (Hr)	25000Hrs

PHOTOMETRIC DATA

Luminous efficacy	100Lm/W
Luminous flux	7000Lm
CCT	300/4000/6500K
CRI	>82
LED manufacturer	MLS
Chip type	SMD 2835
SDCM	≤6
Beam angle	120°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >