צמוד תקרה שחור TIME 64W 800MM IP40 12CCT




סדרת צמודי תקרה בעיצוב דק וביעילות אורית גבוהה במיוחד /135Lm W. כולל שלט לשינוי גוון אור, עמעום ודרייבר איכותי ללא ריצוד. כיסוי פרוסט מונע סנוור. התקנה קלה ונוחה. להארה בחדרי מגורים, משרדים, שטחים מסחריים, מבואות ועוד.

מק"ט - 17830003


דגם - LV800STB

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IP40
- CLASS2
- אייקון של 240-220 וולט 60-50 הרץ
- 3 שנות אחריות







DIMENSIONS & WEIGHT

Height	25mm
Diameter	800mm
Product weight	5150g

MATERIALS & COLORS

Cable surface [mm2]	black
Protection class IEC 62262	ABS
Cover finishing	IK06
Cover material	milky
Lens material	PC

ELECTRICAL DATA

Nominal wattage	64W
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Dimmable mode	Yes

CERTIFICATES & STANDARDS

Nisko Class	ECO 3 Years
Israeli Standard	Ta=45°C IS 20-1 IS 20-2-1
ISI Marking	✓
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
CE	IEC 60598-1 IEC 60598-2-1 IEC 62493
Photobiological Safety	IEC 62471 RG0 (Exempt) IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP40
Protection class IK 62262 (shock resistance)	IK06

APPLICATION & MOUNTING

Ambient temperature range	0...+35°C

PERFORMANCE

Lifespan (Hr)	30000Hrs

PHOTOMETRIC DATA

Luminous efficacy	135Lm/W
Luminous flux	8600Lm
CCT	12CCTK
CRI	>80
LED manufacturer	LVMING
Chip type	SMD 2835
Beam angle	120°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 > קבוצת ניסקו בע"מ > המעיין 41, מודיעין >