# דרייבר לד 800mA 25-42V LIFUD




דרייבר לד 800mA 33-40V LIFUD

מק"ט - 17900109

דגם - LF-GIF040YS0800H

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IP20
- CLASS2
- אייקון של 220-240 וולט 50-60 הרץ
- מוצר בדרגת PRO
- 5 שנות אחריות

# DIMENSIONS & WEIGHT

| | |
|---|---|
| Width | 41mm |
| Length | 115mm |
| Height | 28mm |
| Product weight | 99g |

# MATERIALS & COLORS

| | |
|---|---|
| Cable surface [mm2] | white |
| Protection class IEC 62262 | PC |

# ELECTRICAL DATA

| | |
|---|---|
| Nominal wattage | 20-33W |
| Nominal voltage | 220-240V |
| Mains frequency | 50/60Hz |
| Protection class | Class 2 |
| Driver manufacturer | LIFUD |
| Driver model | LF-GIF040YS0800H |
| Driver output current | 800mA |
| Dimmable mode | No |

# CERTIFICATES & STANDARDS

| | |
|---|---|
| Nisko Class | PROFESSIONAL 5 Years |
| Israeli Standard | Ta=50°C<br>IS 61347-1<br>IS 61347-2-13 |
| CB | IEC 60598-1<br>IEC 61347-1<br>IEC 61347-2-13<br>IEC 62493 |
| EMC | IEC 55015<br>IEC 61000-3-2<br>IEC 61000-3-3<br>IEC 61547 |
| IP 60529 | IP20 |
| ISO 9001 | ✓ |

# APPLICATION & MOUNTING

not an empty array

| | |
|---|---|
| Application environment | Indoor |
| Type of protection | IP20 |
| Ambient temperature range | -30...+45°C |

# PERFORMANCE

| | |
|---|---|
| Lifespan (Hr) | 45000Hrs |