ספוט לד שחור לפס צבירה מגנטי TIKTOK
SPOT 12W 3CCT





ספוט לד מתכוונן למערכת פסי צבירה מגנטיים 48V בעיצוב עדין ואלגנטי, מקדם מסירת צבע גבוה במיוחד CRI>90 וזווית הארה של 36°, הספוט מבליט ומחמיא לאובייקטים ולאלמנטים בהתאם לצרכים, וורסטיליות MIX&MATCH מאפשרת שילובים ומשחקי אור וצל, ליצירת מגוון עצום של פתרונות מודולריים, להארה בבתי מגורים, מלונות, חנויות, מסעדות ועוד,

מק"ט - 19185218
דגם - MY-20-6079 12W BLACK
קישור לדף מוצר ואביזרים נלווים באתר

3 YEAR GUARANTEE | VALUE | 48V | IP40 | IK04 | מתאים לדרישות התקן הישראלי



DIMENSIONS & WEIGHT	מידות ומשקל
Height	100mm
Diameter	46mm
Product weight	140g

MATERIALS & COLORS	מבנה וגימור
Product color	black
Body material	aluminum
Protection class IEC 62262	IK04
Cover finishing	Clear
Cover material	PC

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	12W
Nominal current	0.1A
Nominal voltage	48V
Mains frequency	50/60Hz
Protection class	Class 3
Operating mode	External LED driver
Driver manufacturer	Integrated
Driver output current	250mA
Power factor	>0.53
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
IP 60529	IP40
Protection class IK 62262 (shock resistance)	IK04
ISO 9001	√
מחירון דקל	88.082.0820

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Trackline
Mounting location	Ceiling
Type of protection	IP40
Ambient temperature range	-10...+40°C

PERFORMANCE ביצועים

Lifespan (Hr)	30000Hrs

PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	72Lm/W
Luminous flux	860Lm
CCT	3000/4000/6000K
CRI	>90
LED manufacturer	EVERCORE
Chip type	COB
Beam angle	36°
CIE class	Semi-Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >