
ספוט לד לבן לפס צבירה מגנטי TIKTOK
DOT43 24W 3CCT





ספוט לד למערכת פסי צבירה מגנטיים 48V בעיצוב עדין ואלגנטי של "עיניים",
מקדם מסירת צבע גבוה במיוחד CRI>90 וזווית הארה של 24°, הספוט מבליט
ומחמיא לאובייקטים ולאלמנטים בהתאם לצרכים,
וורסטיליות MIX&MATCH מאפשרת שילובים ומשחקי אור וצל, ליצירת מגוון עצום
של פתרונות מודולריים, להארה בבתי מגורים, מלונות, חנויות, מסעדות ועוד,

מק"ט - 19185265
דגם - MY-20-6201 24W WHITE
קישור לדף מוצר ואביזרים נלווים באתר

3 YEAR GUARANTEE | VALUE | 48V | IP40 | IK04 | מתאים לדרישות התקן הישראלי

DIMENSIONS & WEIGHT	מידות ומשקל
Width	430mm
Length	22mm
Height	23mm
Product weight	210g

MATERIALS & COLORS	מבנה וגימור
Product color	white
Body material	aluminum
Protection class IEC 62262	IK04
Cover finishing	Clear
Cover material	PC
Lens material	PC

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	24W
Nominal current	0.19A
Nominal voltage	48V
Mains frequency	50/60Hz
Protection class	Class 3
Operating mode	External LED driver
Driver manufacturer	Integrated
Driver output current	600mA
Power factor	>0.57
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=25°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
IP 60529	IP40
Protection class IK 62262 (shock resistance)	IK04
ISO 9001	√

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Trackline
Mounting location	Ceiling
Type of protection	IP40
Ambient temperature range	-10...+40°C

PERFORMANCE ביצועים

Lifespan (Hr)	30000Hrs

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	80Lm/W
Luminous flux	1920Lm
CCT	3000/4000/6000K
CRI	>90
LED manufacturer	JF
Chip type	SMD 3030
Beam angle	24°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >