ספוט לד שטוח לבן לפס צבירה מגנטי
TIKTOK FLAT30 10W 30CM 3CCT





תאורה אלגנטית ומדויקת בעיצוב שטוח בקו אפס עם פרופיל המערכת, כולל כיסוי חלבי, מקדם מסירת צבע מרשים במיוחד (CRI>90) ושלושה גווני אור בגוף אחד: חם, ניטרלי וקר, להתאמה מושלמת לצרכים משתנים, מערכת MIX&MATCH מאפשרת משחקי אור וצל ייחודיים, מה שמוביל למגוון רחב של פתרונות תאורה מודולריים ומותאמים אישית, להארה בבתי מגורים, מלונות, חנויות, מסעדות, ועוד,

מק"ט - 19185301

דגם - MY-20-6210 10W WHITE

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IK04
- IP40
- CLASS3
- 48V
- מוצר בדרגת VALUE
- 3 שנות אחריות



DIMENSIONS & WEIGHT

Width	300mm
Length	22mm
Height	23mm
Product weight	60g

MATERIALS & COLORS

Cable surface [mm2]	white
Protection class IEC 62262	aluminum
Cover finishing	IK04
Cover material	milky
Lens material	PC

ELECTRICAL DATA

Nominal wattage	10W
Nominal current	0.09A
Nominal voltage	48V
Mains frequency	50/60Hz
Protection class	Class 3
Operating mode	External LED driver
Driver manufacturer	Integrated
Driver output current	250mA
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	✓
IP 60529	IP40
Protection class IK 62262 (shock resistance)	IK04
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	-10...+40°C

PERFORMANCE

Lifespan (Hr)	30000Hrs

PHOTOMETRIC DATA

Luminous efficacy	85Lm/W
Luminous flux	850Lm
CCT	3000/4000/6000K
CRI	>90
LED manufacturer	JF
Chip type	SMD 2835
Beam angle	120°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 > קבוצת ניסקו בע"מ > המעיין 41, מודיעין >