

פס תאורה לד לבן LASER LED 12W 2CCT

גוף תאורת לד בעיצוב דק ועדין. מפסק הדלקה לבחירת גוון אור חם או קר. לגופים מצורף סט אביזרי חיבור ושרשור גופים נוספים לפתרון מלא ומגוון, כולל התקנה צדית. כיסוי חלבי לפיזור אור אחיד. ייעודי לתאורה נסתרת, תאורת מדף, קרניזים ומטבחים.

מק"ט - 70221209
דגם - LG05BN-09-12-150-TC
קישור לדף מוצר ואביזרים נלווים באתר

מתאים לדרישות התקן הישראלי | IP20 | 220-240V 50-60Hz | 1 YEAR GUARANTEE





DIMENSIONS & WEIGHT	מידות ומשקל
Width	28mm
Length	873mm
Height	36mm
Product weight	304g

MATERIALS & COLORS	מבנה וגימור
Product color	white
Body material	PC
Cover finishing	milky
Cover material	PC

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	12W
Nominal current	0.05A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Driver output current	40-60mA
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	ECO 1 Year
Israeli Standard	Ta=40°C IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20
Green Building	ISO 14001
ISO 9001	√

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Surface
Mounting location	Ceiling Wall
Type of protection	IP20
Ambient temperature range	0...+40°C

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	108Lm/W
Luminous flux	1300Lm
CCT	3000/5000K
CRI	>80
LED manufacturer	WEI ZHI PHOTOELECTRIC
Chip type	SMD 2835
Beam angle	120°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < מודיעין 41, המעיין < קבוצת ניסקו בע"מ