הרמטי KING IP65 75W 3CCT L



סדרת גופי תאורה הרמטיים עם נוכחות מרשימה ביעילות אורית גבוהה של כ- 100Lm/W. פיזור אור אחיד, יעיל וחסכוני בחשמל. דרגת אטימות IP65. אפשרות בחירה לגוון האור - חם, ניטרלי או קר, תוך שימוש במפסק ייעודי. התקנה קלה באמצעות זוג תופסני נירוסטה חיצוניים לשמירה על אטימות הגוף. ניתן לשרשר בין גופים תוך שימוש באנטיגרון נוסף בצידו השני של הגוף. לשימוש ביתי במרפסת שמש, פרגולות, סוכות, מחסנים ביתיים ועוד.

מק"ט - 70337876

דגם - HS-TR15006-F/CCT-L

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IP65
- CLASS2
- אייקון של 220-240 וולט 50-60 הרץ
- 3 שנות אחריות

DIMENSIONS & WEIGHT

Length	1570mm
Height	1570mm
Diameter	78mm

MATERIALS & COLORS

Cable surface [mm2]	white
Protection class IEC 62262	PC
Cover material	milky
Lens material	PC

ELECTRICAL DATA

Nominal wattage	75W
Nominal current	0.32A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Driver output current	270mA
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	ECO 3 Years
Israeli Standard	Ta=25°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP65
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	0...+25°C

PHOTOMETRIC DATA

Luminous efficacy	100Lm/W
Luminous flux	7500Lm
CCT	3000/4000/5000K
CRI	>80
Chip type	SMD 2835
Beam angle	170°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ < המעיין 41, מודיעין