תאורת מראה גוף שחור RAIN IP44 15W אור חם



סדרת גופי תאורת מראה בעיצוב יוקרתי ובדרגת אטימות IP44. כוללים לדים איכותיים מבית LUMILEDS ודרייבר מוביל מבית TRIDONIC. להתקנה נוחה ומהירה בחדרי אמבטיה, מעל המראות ועוד.

מק"ט - 70338020

דגם - 22113

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IK04
- IP44
- CLASS2
- אייקון של 220-240 וולט 50-60 הרץ
- מוצר בדרגת PRO
- 5 שנות אחריות





DIMENSIONS & WEIGHT

Width	85mm
Length	595mm
Height	110mm
Product weight	1890g

MATERIALS & COLORS

Cable surface [mm2]	black
Protection class IEC 62262	aluminum
Cover finishing	IK04
Cover material	Clear
Lens material	PMMA

ELECTRICAL DATA

Nominal wattage	15W
Nominal current	0.07A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	TRIDONIC
Driver model	LC 19/200-350/54 Flex Ip SNC4
Driver output current	200-350mA
Power factor	>0.92
THDi	<14%
Output ripple current	≤5%
Inrush current	15A
Inrush current time T_{h50}	100µs
Max. no. of lum. On circuit break. B10 A	39
Max. no. of lum. On circuit break. B16 A	63
Max. no. of lum. On circuit break. C10 A	65
Max. no. of lum. On circuit break. C16 A	105
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-5 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62384 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP44
Protection class IK 62262 (shock resistance)	IK04
Green Building	ISO 14001
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	-10...+40°C

PERFORMANCE

Lifespan (Hr)	100000Hrs
Driver lifespan	100000Hrs

PHOTOMETRIC DATA

Luminous efficacy	53Lm/W
Luminous flux	800Lm
CCT	3000K
CRI	>90
LED manufacturer	LUMILEDS
Chip type	SMD 2835
Beam angle	120°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >