מנורת קריאה PAGE 3.6W גוף שחור אור חם



גוף תאורה מתכוונן לצד מיטה בעיצוב קלאסי. כיסוי פריזמטי למניעת סנוור ופיזור אור אחיד. רכיבים איכותיים של חברות מובילות בעולם.

מק"ט - 70338033
דגם - 58034
קישור לדף מוצר ואביזרים נלווים באתר

3 YEAR GUARANTEE | VALUE | 220-240V 50-60Hz | IP20 | מתאים לדרישות התקן הישראלי





DIMENSIONS & WEIGHT	מידות ומשקל
Width	60mm
Length	108mm
Diameter	80mm

MATERIALS & COLORS	מבנה וגימור
Product color	black
Body material	aluminum
Cover finishing	Prismatic

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	3.6W
Nominal current	0.04A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	LIFUD
Driver model	LF-GIR003YS0300H(D)
Driver output current	300mA
Output ripple current	≤0.9%
Inrush current	30A
Inrush current time T_{h50}	100µs
Max. no. of lum. On circuit break. B10 A	38
Max. no. of lum. On circuit break. B16 A	60
Max. no. of lum. On circuit break. C10 A	64
Max. no. of lum. On circuit break. C16 A	102
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=50°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
IP 60529	IP20
Green Building	ISO 14001
ISO 9001	√

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Surface
Mounting location	Wall
Type of protection	IP20
Ambient temperature range	0...+50°C

PERFORMANCE ביצועים

Lifespan (Hr)	50000Hrs
Driver lifespan	50000Hrs

PHOTOMETRIC DATA

אופטיקה

Luminous efficacy	56Lm/W
Luminous flux	200Lm
CCT	3000K
CRI	>90
LED manufacturer	CREE
Chip type	COB
Beam angle	45°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >