מנורת קריאה INDEX 3.6W לבן אור חם



גוף תאורה מתכוונן לצד מיטה בעיצוב קלאסי כולל כיסוי תאורה לשומרי שבת.
מאושר לשימוש בשבת וחג ע"פ ההלכה בהתאם להנחיות צומת. כיסוי פריזמטי
למניעת סנוור ופיזור אור אחיד. רכיבים איכותיים של חברות מובילות בעולם. מאושר
לשימוש בשבת ובחג על ידי ההלכה.

מק"ט - 70338038
דגם - DW-W3071-WT
קישור לדף מוצר ואביזרים נלווים באתר

מתאים לדרישות התקן הישראלי | IP20 | 220-240V 50-60Hz | 2 YEAR GUARANTEE



DIMENSIONS & WEIGHT	מידות ומשקל
Width	62mm
Diameter	80mm
Product weight	230g

MATERIALS & COLORS	מבנה וגימור
Product color	white
Body material	aluminum
Cover finishing	Prismatic
Cover material	PC
Lens material	PC

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	3.6W
Nominal current	0.02A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	LIFUD
Driver model	LF-GIR003YS(B)0300H(D)
Driver output current	300mA
Output ripple current	≤0.9%
Inrush current	30A
Inrush current time T_{h50}	100µs
Max. no. of lum. On circuit break. B10 A	38
Max. no. of lum. On circuit break. B16 A	60
Max. no. of lum. On circuit break. C10 A	64
Max. no. of lum. On circuit break. C16 A	102
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	ECO 2 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20
ISO 9001	√

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Surface
Mounting location	Wall
Type of protection	IP20
Ambient temperature range	0...+40°C

PERFORMANCE ביצועים

Lifespan (Hr)	60000Hrs

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	69Lm/W
Luminous flux	250Lm
CCT	3000K
CRI	>90
LED manufacturer	CREE
Chip type	COB
Beam angle	30°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >