הרמטי לד לבן SUPER LED 80W IP65 אור ניטרלי




סדרת גופי תאורת לד הרמטיים ביעילות אורית של כ- 100Lm/W ודרגת אטימות IP65. הגוף מחווט בכבל באורך של 70cm וכולל התקנה נוחה ומהירה, ללא צורך בפתיחת הגוף. להארת מרפסות, פרגולות, סוכות, מחסנים ביתיים ועוד.

מק"ט - 70338480
דגם - OLD-01-1580-F
קישור לדף מוצר ואביזרים נלווים באתר

3 YEAR GUARANTEE | 175-240V 50-60Hz | IP65 | מתאים לדרישות התקן הישראלי





DIMENSIONS & WEIGHT	מידות ומשקל
Width	85mm
Length	1540mm
Height	50mm
Product weight	592g

MATERIALS & COLORS	מבנה וגימור
Product color	white
Body material	PC
Cover finishing	milky
Cover material	PC

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	80W
Nominal current	0.34A
Nominal voltage	175-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Power factor	>0.98
THDi	<6%
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=25°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
CE	IEC 60598-1 IEC 60598-2-1
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP65

APPLICATION & MOUNTING יישומים

Application environment	Indoor Outdoor
Mounting type	Surface
Mounting location	Ceiling Wall
Type of protection	IP65
Ambient temperature range	0...+35°C

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	90Lm/W
Luminous flux	7200Lm
CCT	4000K
CRI	>80
Chip type	SMD 2835
Beam angle	120°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < מודיעין 41, המעיין < קבוצת ניסקו בע"מ