הרמטי חירום HYDRA IP65 33W 4K





סדרה לינארית מקצועית לגופי תאורה דו-תכליתיים IP65. יעילות אורית גבוהה של עד 120lm/w, וחיסכון משמעותי בצריכת החשמל ובתחזוקה לעומת גופי תאורה מסורתיים. פתיחת הגוף באמצעות קליפסים ממתכת, גישה לדרייבר, לקיט חירום ואפשרות לחיווט גם מגב גוף התאורה. תפוקה אורית גבוה במצב חירום של 460 lm ו-5 שנות אחריות. להארת חניונים, מסדרונות, מחסנים, תעשייה, מבני ציבור ועוד.

מק"ט - 71333342
דגם - LG07J-12-33-4K LED WATERPROOF LIGHT 4000K 33W EM
קישור לדף מוצר ואביזרים נלווים באתר

5 YEAR GUARANTEE | PRO | 220-240V 50-60Hz | IP65 | IK08 | מתאים לדרישות התקן הישראלי





DIMENSIONS & WEIGHT — מידות ומשקל

Width	79mm
Length	1205mm
Height	68mm

MATERIALS & COLORS — מבנה וגימור

Product color	gray
Body material	PC
Protection class IEC 62262	IK08
Cover finishing	milky
Cover material	PC
Lens material	PC

NISKO

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	33/6W
Nominal current	0.15A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	HOWLONGER
Driver model	LSN40W024T2
Driver output current	240mA
Power factor	>0.97
THDi	<6%
Output ripple current	≤5%
Inrush current	24.6A
Inrush current time T_{h50}	204µs
Max. no. of lum. On circuit break. B10 A	67
Max. no. of lum. On circuit break. B16 A	83
Max. no. of lum. On circuit break. C10 A	70
Max. no. of lum. On circuit break. C16 A	112
Battery	Li-ion
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	PROFESSIONAL 5 Years Battery 3 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-1 IS 20-2-22
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-7 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
IP 60529	IP65
Protection class IK 62262 (shock resistance)	IK08
Green Building	ISO 14001
ISO 9001	√

APPLICATION & MOUNTING יישומים

Application environment	Indoor Outdoor
Mounting type	Surface
Mounting location	Ceiling Wall
Type of protection	IP65
Ambient temperature range	0...+40°C

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	120Lm/W
Luminous flux	3950/460Lm
CCT	4000K
CRI	>80
LED manufacturer	EVERLIGHT
Chip type	SMD 2835
Beam angle	120°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < מודיעין 41, המעיין < קבוצת ניסקו בע"מ