שקוע תקרה לבן LIME 12W 90mm IP44 3CCT



סדרת שקועי תקרה בעיצוב נקי וגמיש, המאפשרת התאמה פשוטה לחללים שונים.
כל גוף מגיע באריזה אחת עם שתי מסגרות חיצוניות – שחור ולבן – הניתנות להחלפה בקליק, ללא צורך בכלים. הסדרה כוללת בחירת גוון אור מתחלף: חם, ניטרלי או קר, להתאמה מדויקת לאופי החלל ולשימוש היומיומי. זווית הארה של 38° מספקת הארה ממוקדת ונעימה, בשילוב שטף אור גבוה של 110 לומן לוואט.
מתאימה להארה בבתים פרטיים, מסדרונות, חדרי מגורים וחללי פנים נוספים.

מק"ט - 72112302
דגם - 1515K-DL3.5C4W 12W IP44 WHITE
קישור לדף מוצר ואביזרים נלווים באתר

1 YEAR GUARANTEE | 220-240V 50-60Hz | IP20 IP44 | מתאים לדרישות התקן הישראלי



DIMENSIONS & WEIGHT	מידות ומשקל
Height	55mm
Diameter	105mm
Product weight	124g
Cut hole diameter	90mm

MATERIALS & COLORS	מבנה וגימור
Product color	white
Body material	PC
Cover finishing	milky
Cover material	PC

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	12W
Nominal current	0.1A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Driver output current	100mA
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	ECO 1 Year
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-2
CE	IEC 60598-1 IEC 60598-2-2 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
IP 60529	IP20/IP44

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Recessed
Mounting location	Ceiling
Type of protection	IP20/IP44
Ambient temperature range	-10...+35°C

PERFORMANCE ביצועים

Lifespan (Hr)	30000Hrs

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	117Lm/W
Luminous flux	1400(3K)Lm
CCT	2700/4200/6500K
CRI	>80
LED manufacturer	HONGLITRONIC
Chip type	SMD 2835
Beam angle	38°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < מודיעין 41, המעיין < קבוצת ניסקו בע"מ