
צמוד תקרה זהב JULIA 40W 40CM 3CCT






סדרת גופי תאורה צמודי תקרה דקורטיביים, בעיצוב מודרני ואלגנטי, המציעים שילוב מושלם של פונקציונליות ואסתטיקה. מאפשרים בחירה בין שלושה גווני אור – חם, ניטרלי או קר – להתאמה אישית לכל חלל וליצירת האווירה הרצויה. שטף אורי גבוה, דרייבר איכותי ללא ריצוד וכיסוי אופטי חלבי המבטיח פיזור אור אחיד ונעים, ללא סנוור, לתאורה נוחה ונעימה. חיסכון משמעותי בצריכת חשמל. להארת חדרי מגורים, מסעדות, בתי מלון, חללים מסחריים ועוד.

מק"ט - 74083420

דגם - A-MBMZH60H-R400 GOLD

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IP20
- CLASS1
- אייקון של 220-240 וולט 50-60 הרץ
- 3 שנות אחריות





DIMENSIONS & WEIGHT

Height	60mm
Diameter	400mm
Product weight	1450g

MATERIALS & COLORS

Cable surface [mm2]	gold
Protection class IEC 62262	aluminum
Cover material	milky
Lens material	PC

ELECTRICAL DATA

Nominal wattage	40W
Nominal current	0.182A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	LIFUD
Driver model	LF-GIF040ES1050H
Driver output current	1050mA
Power factor	>0.98
THDi	<15%
Output ripple current	≤5%
Inrush current	30A
Inrush current time T_{h50}	150µs
Max. no. of lum. On circuit break. B10 A	26
Max. no. of lum. On circuit break. B16 A	44
Max. no. of lum. On circuit break. C10 A	43
Max. no. of lum. On circuit break. C16 A	71
Dimmable mode	ON/OFF dimmable optional
Optional driver ON/OFF	LF 17900112 LDV 10025040
Optional driver 1-10V	LF 17900218
Optional driver DALI	LF 17900254 LF 17900259
Optional driver TRIAC	LF 17900034

CERTIFICATES & STANDARDS

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	✓
IP 60529	IP20

APPLICATION & MOUNTING

Ambient temperature range	-10...+35°C

PERFORMANCE

Lifespan (Hr)	40000Hrs
Driver lifespan	40000Hrs

PHOTOMETRIC DATA

Luminous efficacy	108Lm/W
Luminous flux	4300(4K)Lm
CCT	3000/4000/6000K
CRI	>80
LED manufacturer	MLS
Chip type	SMD 2835
Beam angle	120°
CIE class	Direct
Efficiency	100%