צמוד תקרה מרחף לבן GALAXY 40W 40CM 3CCT



סדרת צמודי תקרה דקורטיביים מרחפים, בעלי מסגרת דקה ואלגנטית. הגופים מייצרים עוצמה אורית גבוהה ומאפשרים בחירה בין שלושה גווני אור – חם, ניטרלי או קר, להתאמה אישית בכל חלל וליצירת האווירה הרצויה. הכיסוי האופטי החלבי מבטיח פיזור אור אחיד ונעים, ללא סנוור, להשגת תאורה נוחה ונעימה. חסכוניים בצריכת חשמל, ומצוידים בדרייבר איכותי ללא ריצוד. להארת חדרי מגורים, מסעדות, בתי מלון, חללים מסחריים ועוד.

מק"ט - 74094001
דגם - A-MBMZH11-R400 WHITE
קישור לדף מוצר ואביזרים נלווים באתר







DIMENSIONS & WEIGHT מידות ומשקל

Height	47mm
Diameter	392mm
Product weight	1450g

MATERIALS & COLORS מבנה וגימור

Product color	white
Body material	aluminum
Cover finishing	milky
Cover material	PS
Lens material	PMMA

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	40W
Nominal current	0.16A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	LIFUD
Driver model	LF-GIF040ES0900H
Driver output current	900mA
Power factor	>0.96
THDi	<15%
Output ripple current	≤5%
Inrush current	30A
Inrush current time T_{h50}	150µs
Max. no. of lum. On circuit break. B10 A	26
Max. no. of lum. On circuit break. B16 A	43
Max. no. of lum. On circuit break. C10 A	44
Max. no. of lum. On circuit break. C16 A	71
Dimmable mode	ON/OFF dimmable optional
Optional driver ON/OFF	LF 17900111 LDV 10025040
Optional driver 1-10V	LF 17900215 LF 17900218
Optional driver DALI	LF 17900258
Optional driver TRIAC	LF 17900034

CERTIFICATES & STANDARDS תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
IP 60529	IP20

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Surface
Mounting location	Wall
Type of protection	IP20
Ambient temperature range	-10...+35°C

PERFORMANCE ביצועים

Lifespan (Hr)	40000Hrs

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	90Lm/W
Luminous flux	3600Lm
CCT	3000/4000/6000K
CRI	>80
LED manufacturer	MLS
Chip type	SMD 2835
Beam angle	120°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ < המעיין 41, מודיעין