צמוד תקרה מרחף שחור GALAXY 75W 80CM 3CCT





סדרת צמודי תקרה דקורטיביים מרחפים, בעלי מסגרת דקה ואלגנטית. הגופים מייצרים עוצמה אורית גבוהה ומאפשרים בחירה בין שלושה גווני אור – חם, ניטרלי או קר, להתאמה אישית בכל חלל וליצירת האווירה הרצויה. הכיסוי האופטי החלבי מבטיח פיזור אור אחיד ונעים, ללא סנוור, להשגת תאורה נוחה ונעימה. מסכוניים בצריכת חשמל, ומצוידים בדרייבר איכותי ללא ריצוד. להארת חדרי מגורים, מסעדות, בתי מלון, חללים מסחריים ועוד.

מק"ט - 74094013

דגם - A-MBMZH11-R800 BLACK

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IP20 IP40
- CLASS1
- אייקון של 220-240 וולט 50-60 הרץ
- 3 שנות אחריות





DIMENSIONS & WEIGHT

Height	47mm
Diameter	768mm
Product weight	4700g

MATERIALS & COLORS

Cable surface [mm2]	black
Protection class IEC 62262	aluminum
Cover material	milky
Lens material	PS

ELECTRICAL DATA

Nominal wattage	75W
Nominal current	0.33A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	LIFUD
Driver model	2 × LF-GIF040ES0900H
Driver output current	1800mA
Power factor	>0.96
THDi	<15%
Output ripple current	≤5%
Inrush current	60A
Inrush current time T_{h50}	150µs
Max. no. of lum. On circuit break. B10 A	13
Max. no. of lum. On circuit break. B16 A	21
Max. no. of lum. On circuit break. C10 A	22
Max. no. of lum. On circuit break. C16 A	35
Dimmable mode	ON/OFF dimmable optional
Optional driver ON/OFF	LF 17900111 LDV 10025040
Optional driver 1-10V	LF 17900215 LF 17900218
Optional driver DALI	LF 17900258
Optional driver TRIAC	LF 17900034

CERTIFICATES & STANDARDS

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	✓
IP 60529	IP20
מחירון דקל	88.082.1010

APPLICATION & MOUNTING

Ambient temperature range	-10...+35°C

PERFORMANCE

Lifespan (Hr)	40000Hrs

PHOTOMETRIC DATA

Luminous efficacy	90Lm/W
Luminous flux	6750Lm
CCT	3000/4000/6000K
CRI	>80
LED manufacturer	MLS
Chip type	SMD 2835
Beam angle	120°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < מודיעין 41, המעיין < קבוצת ניסקו בע"מ