צמוד תקרה צילינדר לבן חלבי DARIA 15W 3CCT




צילינדר המאיר מעלה ומטה, ומציג טכנולוגיה מתקדמת, עיצוב חדשני, מוקפד ונקי. מיועד להדגשת קירות וליצירת אווירה אינטימית בחללים מגוונים. כולל דרייבר חיצוני ללא ריצוד, התקנה קלה ונוחה במגוון רחב של יישומים. מאפשר שילוב אסתטי ופונקציונלי בהתאמה לצרכים שונים. משתלב באופן מושלם בבתי מגורים, חללי עבודה, גלריות ובתי מלון.


מק"ט - 75410441


דגם - 386A-115-15W-C3 WHITE 3CCT

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IP40
- CLASS1
- אייקון של 220-240 וולט 50-60 הרץ
- מוצר בדרגת VALUE
- 3 שנות אחריות







DIMENSIONS & WEIGHT

Height	94mm
Diameter	115mm
Product weight	580g

MATERIALS & COLORS

Cable surface [mm2]	white
Protection class IEC 62262	aluminum
Cover material	milky
Lens material	PC

ELECTRICAL DATA

Nominal wattage	14W
Nominal current	0.06A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver output current	350mA
Power factor	>0.96
THDi	<11%
Output ripple current	≤3%
Inrush current	7.8A
Inrush current time T_{h50}	34.9µs
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	✓
IP 60529	IP40
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	-20...+40°C

PERFORMANCE

Lifespan (Hr)	30000Hrs

PHOTOMETRIC DATA

Luminous efficacy	89Lm/W
Luminous flux	1150/1250/1300Lm
CCT	3000/4000/5700K
CRI	>90
LED manufacturer	RUNLITE
Chip type	SMD 2835
Beam angle	100°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >