צילינדר TWIST 7W 3CCT גוף לבן עם עץ



סדרת הצילינדרים המעוצבים של TWIST. צמודי תקרה, מתכווננים ב- 350 מעלות, עשויים מאלומיניום איכותי, ובעלי איכות אורית גבוהה CRI>90. כיסוי אקרילי חלבי להבטחת פיזור אור אחיד ולמניעת סינוור בזווית הארה של 110 מעלות. כולל FLICKER FREE. התקנה קלה ונוחה. אידיאלי להתקנה בבתי מגורים, גלריות, בתי מלון, חנויות, מסעדות, מעברים ועוד.

מק"ט - 75410506
דגם - UNI-ICSM-201WW-CCT
קישור לדף מוצר ואביזרים נלווים באתר

3 YEAR GUARANTEE | VALUE | 100-240V 50-60Hz | IP20 | מתאים לדרישות התקן הישראלי



DIMENSIONS & WEIGHT	מידות ומשקל
Height	60mm
Diameter	76mm
Product weight	300g

MATERIALS & COLORS	מבנה וגימור
Product color	לבן עץ
Body material	PC
Cover finishing	milky
Cover material	PMMA
Lens material	PMMA

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	7.2W
Nominal current	0.03A
Nominal voltage	100-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver output current	200mA
Power factor	>0.90
THDi	<15%
Output ripple current	≤2%
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20
ISO 9001	√

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Surface
Mounting location	Wall
Type of protection	IP20
Ambient temperature range	0...+35°C

PERFORMANCE ביצועים

Lifespan (Hr)	30000Hrs

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	64Lm/W
Luminous flux	460Lm
CCT	3000/4000/6000K
CRI	>90
LED manufacturer	OSRAM
Chip type	SMD 2835
Beam angle	110°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < מודיעין 41, המעיין < קבוצת ניסקו בע"מ