צילינדר TWIST 12W 3CCT גוף לבן עם זהב



סדרת הצילינדרים המעוצבים של TWIST. צמודי תקרה, מתכווננים ב-350 מעלות, עשויים מאלומיניום איכותי, ובעלי איכות אורית גבוהה CRI>90. כיסוי אקרילי חלבי להבטחת פיזור אור אחיד ולמניעת סינוור בזווית הארה של 110 מעלות. כולל FLICKER FREE. התקנה קלה ונוחה. אידיאלי להתקנה בבתי מגורים, גלריות, בתי מלון, חנויות, מסעדות, מעברים ועוד.

מק"ט - 75410512

דגם - UNI-ICSM-202WG-CCT

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IP20
- CLASS1
- 100-240 וולט 50-60 הרץ
- מוצר בדרגת VALUE
- 3 שנות אחריות



DIMENSIONS & WEIGHT

Height	60mm
Diameter	120mm
Product weight	550g

MATERIALS & COLORS

Cable surface [mm2]	White/gold
Protection class IEC 62262	PC
Cover material	milky
Lens material	PMMA

ELECTRICAL DATA

Nominal wattage	11W
Nominal current	0.05A
Nominal voltage	100-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver output current	300mA
Power factor	>0.95
THDi	<15%
Output ripple current	≤2%
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	VALUE 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CE	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	0...+35°C

PERFORMANCE

Lifespan (Hr)	30000Hrs

PHOTOMETRIC DATA

Luminous efficacy	75Lm/W
Luminous flux	830Lm
CCT	3000/4000/6000K
CRI	>90
LED manufacturer	OSRAM
Chip type	SMD 2835
Beam angle	110°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 > קבוצת ניסקו בע"מ > המעיין 41, מודיעין