# מנורת תליה AVINO 45W 35CM גוף בצבע קרם אור חם




סדרת גופי תלייה דקורטיביים מסדרת AVINO, המשלבת עיצוב יוקרתי עם נוכחות מרשימה. מגיעה בגווני קרם, ירוק ייחודי ושחור, וכוללת מוט דקורטיבי המעניק מראה אלגנטי, נקי ומוקפד. הסדרה מתאימה לחללים מודרניים ומעוצבים ומציעה תאורה איכותית בהספקים של 46W ו-55W. להארת בתי מגורים, אירוח, מבואות, בתי מלון ועוד.

מק"ט - 75410661
דגם - PD614S-350
קישור לדף מוצר ואביזרים נלווים באתר

3 YEAR GUARANTEE | 220-240V 50-60Hz | IP20 | מתאים לדרישות התקן הישראלי






| DIMENSIONS & WEIGHT | מידות ומשקל |
|---|---|
| Height | 85mm |
| Diameter | 350mm |
| Product weight | 1500g |
| Cable length | Approx. 2 meters |

| MATERIALS & COLORS | מבנה וגימור |
|---|---|
| Product color | RAL 1013 Cream |
| Body material | aluminum |
| Cover finishing | milky |
| Cover material | PC |
| Lens material | PC |

## ELECTRICAL DATA נתונים חשמליים

| | |
|---|---|
| Nominal wattage | 46W |
| Nominal current | 0.2A |
| Nominal voltage | 220-240V |
| Mains frequency | 50/60Hz |
| Protection class | Class 1 |
| Operating mode | External LED driver |
| Driver manufacturer | EAGLERISE |
| Driver model | LS-50-1200 LI EXC |
| Driver output current | 1200mA |
| Power factor | >0.95 |
| THDi | <10% |
| Output ripple current | ≤3% |
| Inrush current | 33.6A |
| Inrush current time $T_{h50}$ | 148µs |
| Max. no. of lum. On circuit break. B10 A | 16 |
| Max. no. of lum. On circuit break. B16 A | 26 |
| Max. no. of lum. On circuit break. C10 A | 27 |
| Max. no. of lum. On circuit break. C16 A | 44 |
| Dimmable mode | ON/OFF dimmable optional |
| Optional driver ON/OFF | LF 17900114 |
| Optional driver 1-10V | LF 17900211 |
| Optional driver DALI | LF 17900254<br>LF 17900259 |

## CERTIFICATES & STANDARDS תקנים

| | |
|---|---|
| Nisko Class | ECO 3 Years |
| Israeli Standard | Ta=35°C<br>IS 20-1<br>IS 20-2-1 |
| CB | IEC 60598-1<br>IEC 60598-2-1<br>IEC 61347-1<br>IEC 61347-2-13<br>IEC 62031<br>IEC 62493 |
| Photobiological Safety | IEC 62778 RG0 (Exempt) |
| EMC | IEC 55015<br>IEC 61000-3-2<br>IEC 61000-3-3<br>IEC 61547 |
| IP 60529 | IP20 |

## APPLICATION & MOUNTING יישומים

| | |
|---|---|
| Application environment | Indoor |
| Mounting type | Suspension |
| Mounting location | Ceiling |
| Type of protection | IP20 |
| Ambient temperature range | 0...+35°C |

## PHOTOMETRIC DATA אופטיקה

| | |
|---|---|
| Luminous efficacy | 61Lm/W |
| Luminous flux | 2800Lm |
| CCT | 3000K |
| CRI | >90 |
| LED manufacturer | OSRAM |
| Chip type | SMD 2835 |
| Beam angle | 112° |
| Efficiency | 100% |


www.niskoelec.com < info@niskoelec.com < 072-2400-600 < מודיעין 41, המעיין < קבוצת ניסקו בע"מ