מנורת תליה ALURA 50W 50CM גוף בצבע שמפניה אור חם



סדרת גופי התלייה הדקורטיביים ALURA משלבת עיצוב יוקרתי עם קווים נקיים ואלגנטיים. הסדרה מגיעה בגוונים הקלאסיים שחור, לבן ושמפניה ייחודי, ומשלבת אלמנט בגימור זהב המעניק מראה יוקרתי ומוקפד. עם הספקים של 40W, 32W ו-50W. גופי תאורה של סדרת ALURA מספקים תאורה איכותית ואחידה ומשתלבים באופן מושלם בחללים מודרניים ומעוצבים – בבתים, במשרדים, במבואות ובבתי מלון.

מק"ט - 75410688
דגם - PD602-A CHAMP
קישור לדף מוצר ואביזרים נלווים באתר

3 YEAR GUARANTEE | 220-240V 50-60Hz | IP20 | מתאים לדרישות התקן הישראלי





DIMENSIONS & WEIGHT	מידות ומשקל
Height	50mm
Diameter	500mm
Product weight	2500g
Cable length	Approx. 2 meters

MATERIALS & COLORS	מבנה וגימור
Product color	RAL 1035 Champagne
Body material	aluminum
Cover finishing	milky
Cover material	PC
Lens material	PC

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	50W
Nominal current	0.22A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	External LED driver
Driver manufacturer	EAGLERISE
Driver model	LS-50-1250 LI EXC
Driver output current	1250mA
Power factor	>0.95
THDi	<10%
Output ripple current	≤3%
Inrush current	33.6A
Inrush current time T_{h50}	148µs
Max. no. of lum. On circuit break. B10 A	16
Max. no. of lum. On circuit break. B16 A	26
Max. no. of lum. On circuit break. C10 A	27
Max. no. of lum. On circuit break. C16 A	44
Dimmable mode	ON/OFF dimmable optional
Optional driver ON/OFF	LF 17900114
Optional driver DALI	LF 17900254 LF 17900259

CERTIFICATES & STANDARDS תקנים

Nisko Class	ECO 3 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20

APPLICATION & MOUNTING יישומים

Application environment	Indoor
Mounting type	Suspension
Mounting location	Ceiling
Type of protection	IP20
Ambient temperature range	0...+35°C

PERFORMANCE ביצועים

Lifespan (Hr)	50000Hrs

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	60Lm/W
Luminous flux	3000Lm
CCT	3000K
CRI	>90
LED manufacturer	OSRAM
Chip type	SMD 2835
Beam angle	115°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < מודיעין 41, המעיין < קבוצת ניסקו בע"מ