בולרד שחור SYLVANIA 12W 500 mm IP65 אור חם



בולרד איכותי מבית SYLVANIA העולמית. חוזק מכני IK08 ודרגת אטימות IP65. להארת שטחים פתוחים: שבילים, גינות, גנים ציבוריים, מבואות מבנים, טיילות ועוד.

מק"ט - 75512305

דגם - ZT701F-H50B

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IK08
- IP65
- CLASS1
- אייקון של 240-220 וולט 60-50 הרץ
- מוצר בדרגת PRO
- 5 שנות אחריות







DIMENSIONS & WEIGHT

Height	500mm
Diameter	118mm
Product weight	2300g

MATERIALS & COLORS

Cable surface [mm2]	black
Protection class IEC 62262	aluminum
Cover finishing	IK08
Cover material	Clear
Lens material	PC

ELECTRICAL DATA

Nominal wattage	12W
Nominal current	0.06A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	EAGLERISE
Driver model	EBP012C0500CHP
Driver output current	500mA
Power factor	>0.93
Inrush current	10A
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	✓
TM21	√ Ta=35°C
IP 60529	IP65
Protection class IK 62262 (shock resistance)	IK08
Green Building	✓
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	-30...+45°C

PERFORMANCE

Lifespan (Hr)	43800Hrs
TM21	√ Ta=35°C
Lifespan L70	>54000Hrs
Lifespan L80	>54000Hrs
Lifespan L90	>54000Hrs
Driver lifespan	43800Hrs

PHOTOMETRIC DATA

Luminous efficacy	92Lm/W
Luminous flux	1100Lm
CCT	3000K
CRI	>80
LED manufacturer	Lextar
Chip type	SMD 2835
Beam angle	300°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < מודיעין 41, המעיין < קבוצת ניסקו בע"מ