
בולרד שחור SYLVANIA 25W 1000mm IP65 אור חם




בולרד דקורטיבי מבית SYLVANIA העולמית. חוזק מכני IK08 ודרגת אטימות IP65.
להארת שטחים פתוחים: שבילים, גינות, גנים ציבוריים, מבואות מבנים, טיילות ועוד.

מק"ט - 75525310
דגם - ZT714F-H100
קישור לדף מוצר ואביזרים נלווים באתר

5 YEAR GUARANTEE | PRO | 220-240V 50-60Hz | IP65 | IK08 | מתאים לדרישות התקן הישראלי







DIMENSIONS & WEIGHT — מידות ומשקל

Height	1000mm
Diameter	168mm
Product weight	5300g

MATERIALS & COLORS — מבנה וגימור

Product color	black
Body material	aluminum
Protection class IEC 62262	IK08
Cover finishing	Clear
Cover material	PC

NISKO

SYLVANIA

ELECTRICAL DATA נתונים חשמליים

Nominal wattage	25W
Nominal current	0.12A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	EAGLERISE
Driver model	EBP025C1200CHP
Driver output current	1200mA
Power factor	>0.93
Inrush current	10A
Dimmable mode	No

CERTIFICATES & STANDARDS תקנים

Nisko Class	PROFESSIONAL 5 Years
Israeli Standard	Ta=35°C IS 20-1 IS 20-2-1
CB	IEC 60598-1 IEC 60598-2-1 IEC 61347-1 IEC 61347-2-13 IEC 62031
Photobiological Safety	IEC 62778 RG0 (Exempt)
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
LM80	√
TM21	√ Ta=35°C
IP 60529	IP65
Protection class IK 62262 (shock resistance)	IK08
Green Building	√
ISO 9001	√

APPLICATION & MOUNTING יישומים

Application environment	Outdoor
Mounting type	External
Mounting location	Ground
Type of protection	IP65
Ambient temperature range	-30...+45°C

PERFORMANCE ביצועים

Lifespan (Hr)	30000Hrs
TM21	√ Ta=35°C
Lifespan L70	>54000Hrs
Lifespan L80	>54000Hrs
Lifespan L90	>54000Hrs
Driver lifespan	30000Hrs

PHOTOMETRIC DATA אופטיקה

Luminous efficacy	76Lm/W
Luminous flux	1900Lm
CCT	3000K
CRI	>80
LED manufacturer	Lextar
Chip type	SMD 2835
Beam angle	310°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >