
חד תכליתי על הטיח MOON 3W





תאורת חירום עגולה חד תכליתית צמודת תקרה, מיועדת להארת נתיבי מילוט על פי תקן 1838 וכוללת יחידת בקרה לבדיקת סוללה, ממיר, מתח טעינה ופריקה. יחידת הבקרה פועלת באופן עצמאי ואוטומטי לחלוטין - חודשית ושנתית. היחידה כוללת חיווי ויזואלי ע"י נורת לד לפעילות ותקלות. בנוסף, קיים לחצן טסט לבדיקה ידנית. זמן פעולה בשעת חירום כ- 180 דקות. ייעודית לנתיבי מילוט, מסדרונות, בתי מלון, משרדים ומגדלי מגורים.

מק"ט - 77703017

דגם - SDR120

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IP20
- CLASS2
- אייקון של 220-240 וולט 50-60 הרץ
- מוצר בדרגת PRO
- 5 שנות אחריות

DIMENSIONS & WEIGHT

Height	39.5mm
Diameter	120.5mm

MATERIALS & COLORS

Cable surface [mm2]	white
Protection class IEC 62262	PC
Cover material	Clear
Lens material	PC

ELECTRICAL DATA

Nominal wattage	3W
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Battery	Li-ion
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	PROFESSIONAL 5 Years Battery 5 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-22
CB	IEC 60598-1 IEC 60598-2-1 IEC 60598-2-22:2021 IEC 61347-1 IEC 61347-2-7 IEC 62031 IEC 62493 IEC 62133 IEC 62620
Photobiological Safety	IEC 62778 RG1
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP20
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	0...+40°C

PERFORMANCE

Working time off-grid (±5%)	180Min

PHOTOMETRIC DATA

Luminous flux	250Lm
CCT	4000K
LED manufacturer	SMALITE
Beam angle	125°
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 < קבוצת ניסקו בע"מ > המעיין 41, מודיעין >