

תאורת חירום חד תכליתית שחור SPACE 3W אור קר





תאורת חירום חד תכליתית צמודת תקרה בדרגת אטימות IP54. זמן פעולה בשעת חירום - 180 דקות. סוללת ליתיום איכותית, העומדת במספר רב של מחזורי טעינה. יחידת בקרה מובנית לבדיקת סוללה, ממיר, מתח טעינה ופריקה. יחידת בקרה הפועלת עצמאית בחיווי ויזואלי ע"י נורת לד בחלקו הקדמי של המוצר. באישור מכון התקנים ובהתאמה לדרישות תקנות הבנייה. מיועדת להארת נתיבי מילוט במשרדים, חניונים, מבנה מגורים, מרלוג"ים, מפעלים, אזורי עבודה ומוסדות ציבור.


מק"ט - 77703126

דגם - Emergency BY-T1403S 3W IP54 IK08 black

קישור לדף מוצר ואביזרים נלווים באתר

- מתאים לדרישות התקן הישראלי
- IK08
- IP20
- CLASS2
- אייקון של 220-240 וולט 50-60 הרץ
- מוצר בדרגת VALUE
- 3 שנות אחריות





DIMENSIONS & WEIGHT

Height	42mm
Diameter	140mm
Product weight	300g

MATERIALS & COLORS

Cable surface [mm2]	black
Protection class IEC 62262	PC
Cover finishing	IK08
Cover material	Clear
Lens material	PC

ELECTRICAL DATA

Nominal wattage	3/1W
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 2
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Battery	Li-ion
Dimmable mode	No

CERTIFICATES & STANDARDS

Nisko Class	VALUE 3 Years Battery 2 Years
Israeli Standard	Ta=40°C IS 20-1 IS 20-2-22
CB	IEC 60598-1 IEC 60598-2-22 IEC 61347-1 IEC 61347-2-7 IEC 61347-2-11 IEC 60335-1 IEC 62031 IEC 62493
Photobiological Safety	IEC 62778 RG1
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP54
Protection class IK 62262 (shock resistance)	IK08
Green Building	ISO 14001
ISO 9001	✓

APPLICATION & MOUNTING

Ambient temperature range	0...+40°C

PERFORMANCE

Working time off-grid (±5%)	180Min

PHOTOMETRIC DATA

Luminous flux	165Lm
CCT	6500K
CRI	>70
LED manufacturer	Lumen Pioneer Opto
Chip type	SMD 3535
Beam angle	140°
CIE class	Direct
Efficiency	100%

www.niskoelec.com < info@niskoelec.com < 072-2400-600 > מודיעין ,41 המעיין > קבוצת ניסקו בע"מ